



1400 Series

Hot-Water Pressure Washers with 3450 RPM Motors

#1 in North America for High-Pressure Cleaning Equipment

Electric / Belt Drive

Upright, oil-fired burner delivers high efficiency and maintains constant temperature using diesel fuel, kerosene or home-heating oil



Heater coil carries a 5-year warranty

Model 1452SS with Natural Gas-Fired combustion chamber (Shown with optional hose reel)



8.2 HP Baldor, 3450 RPM electric motor is drip proof and comes with thermal overload protection

Stainless-steel coil skin provides extra durability to withstand the elements, resist corrosion and endure rough treatment

50-ft. length of high-pressure hose and hanger for ease in cleaning around a large area

Thermal rupture disk protects the machine and user from thermal expansion

Adjustable upstream detergent injection provides high-pressure sudsing for better cleaning

Easy to understand **operating instructions** and warning labels

Water-resistant cabinet, electrical box and motor

Control panel includes adjustable temperature control, plus heavy-duty heater and pump motor switches

Convenient **hose reel bracket** (standard) accepts swivel or stationary reels

Built-in wand holder provides convenient storage



Hotsty-designed triplex belt-drive pump carries a 7-year limited warranty

Rust-proof, removable, non-contaminating polyethylene fuel tank includes fuel gauge in cap. Tank is oversized to provide for long-running operating time (standard on oil-fired models)

Wheel kit and handle make for easy portability (standard on oil-fired models)

Heavy-duty fuel filter protects burner fuel pump

Model 1450SS: Oil-Fired, 3.9 GPM @ 3000 PSI

Semi-pneumatic tires eliminate the risk of flats

Float tank helps maintain constant water pressure and flow and helps prevent sediment from entering the machine's components...great for use in well-water environments and low-water situations



Insulated Hotsty Trigger Gun, rated to 3750 PSI. **36" insulated wand** with ergonomic, adjustable side handle

FEATURES

- 3.9 GPM @ 3000 PSI
- Oil-Fired or Natural Gas-Fired
- 208V or 230V, 1PH; 208V, 230V, 460V or 575V, 3PH
- ETL-Certified to UL-1776 safety standards

www.Hotsty.com

Nothing Cleans Like a Hotsty!

1400 SERIES Hot-Water ELECTRIC Models with 3450 RPM Motors

- Oil-Fired or Natural Gas-Fired
- 3.9 GPM @ 3000 PSI
- Hotsy Triplex Pump with 7-yr warranty
- ETL-Certified for safety

Designed for tough, industrial cleaning.

SPECIFICATIONS

BELT DRIVE

MODEL	GPM	PSI	HP	MOTOR RPM	VOLT/PH	AMP	FUEL	BTU/HR	PUMP	PUMP RPM	PORTABILITY	HOSE	SHIP WT (lbs)
1450SS	3.9	3000	8.2	3450	230/1	40	Oil	342,900	Hotsy Triplex	1390	Std	50'	650
1450SS-208	3.9	3000	8.2	3450	208/1	44	Oil	342,900	Hotsy Triplex	1390	Std	50'	650
1452SS	3.9	3000	8.2	3450	230/1	40	NG	364,835	Hotsy Triplex	1390	N/A	50'	620
1452SS-208	3.9	3000	8.2	3450	208/1	42	NG	364,835	Hotsy Triplex	1390	N/A	50'	615
1460SS	3.9	3000	8.2	3450	230/3	24	Oil	342,900	Hotsy Triplex	1390	Std	50'	645
1460SS-208	3.9	3000	8.2	3450	208/3	25	Oil	342,900	Hotsy Triplex	1390	Std	50'	645
1462SS	3.9	3000	8.2	3450	230/3	22	NG	364,835	Hotsy Triplex	1390	N/A	50'	615
1462SS-208	3.9	3000	8.2	3450	208/3	23	NG	364,835	Hotsy Triplex	1390	N/A	50'	645
1463SS	3.9	3000	8.2	3450	460/3	12	Oil	342,900	Hotsy Triplex	1390	Std	50'	645
1464SS	3.9	3000	8.2	3450	460/3	11	NG	364,835	Hotsy Triplex	1390	N/A	50'	615
1467SS	3.9	3000	8.2	3450	575/3	11	Oil	342,900	Hotsy Triplex	1390	Std	50'	645
1469SS	3.9	3000	8.2	3450	575/3	10	NG	364,835	Hotsy Triplex	1390	N/A	50'	615

Dimensions: 45"l x 18"w x 48"h

OPTIONS for 1400 SERIES with 3450 RPM Motors

- **Remote Controls:** Controls the start up, shut down and with the optional detergent kit, the application of soap with easy to use low voltage switches.
- **Auto Start/Stop:** Controls starting of the machine by simply triggering the gun. A preset adjustable timer automatically shuts the machine off before damage can occur to pump seals and packings by leaving the machine in by-pass mode.
- **Thermal Pump Protection:** The thermal protector monitors the temperature of the by-passed water and automatically shuts the machine off before temperatures are reached that can damage pump components.
- **Time Delay Shut Down:** Safeguards damage to the machine if the operator fails to shut down the machine after use.
- **LP Conversion Kit:** Converts natural gas fired machines to LP fired machines.
- **Auto-Start with Thermal Shut Down:** Controls starting the machine by simply triggering the gun. Also, if the operator fails to shut off the machine after use, safeguards damage to the machine, before temperatures are achieved where damage can occur.
- **Time Delay with Thermal Shut Down:** A preset adjustable timer is set to automatically shut the machine off, while a thermal protector monitors machine temperature of the by-passed water, also enabling the machine to shut down before damage occurs.
- **8" Natural Gas or LP Gas Fired Draft Diverters** prevent backdrafts; keeps cold air out and prevents water from running down vent pipes.
- **8" Oil-Fired Draft Dampener;** barometric; prevent backdrafts; keeps cold air out and prevents water from running down vent pipes.

Clean better with Hotsy detergents

Hotsy pressure washers clean best when matched with our specially-formulated Hotsy detergents. Nearly all 40 Hotsy detergent formulations contain Hotsy's

exclusive advanced-formula HCC additives to help prevent scale build-up and fight corrosion in your equipment. Most Hotsy detergents are USDA and Canadian Agriculture approved. All are highly concentrated, so a little goes a long way.

Distributed by:



Tel: (800) 525-1976 Fax: (888) 880-9631
 www.Hotsy.com email: info@Hotsy.com
 P/N 97-04227 Effective 1/07 Specifications & product descriptions subject to change without notice. ©2007 Hotsy



Hotsy Accessories customize your application for top performance



360° Pivot and non-pivot hose reels keep hose neatly stored and shop areas safe



High-pressure turbo nozzles for faster cleaning

Telescoping wands extend to 24' to reach high places without scaffolding



Heavy-duty, high-pressure hoses in lengths up to 150-ft.



Rotary surface cleaner attaches to your pressure washer; reduces overspray and zebra striping

NOTE: We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We attempt to keep our machine performance within ± 5% of listed specifications.