



BD / BDE Series

Cold Water Pressure Washers

Gasoline / Electric Belt Drive

#1 in North America for High-Pressure Cleaning Equipment

The BDE and three BD Series models feature a **large cage, 4-wheel** configuration

Heavy-duty **lifting eye**

Choice of **Honda, Vanguard** or **Kohler** engines or Baldor motor

Unibody design for durability and less vibration

Five, high-pressure **stainless steel nozzles**: 0°, 15°, 25°, 40° and a detergent nozzle

High-pressure relief valve protects the machine and user

Heavy-duty **inlet water filter** with removable screen for easy cleaning

Unique heavy-duty roll-cage chassis protects internal components

Totally enclosed **OSHA-compliant belt guard** reduces noise and vibration

All-steel frame with powder coat paint

Downstream detergent injection allows remote detergent injection



Heavy-duty Hotsy Triplex pump comes with 7-year warranty



Trigger gun control with cool-grip

50 ft. wire-braided hose includes guards, couplers and swivels at both ends

13" tubed pneumatic tires for easy handling



Electric Model BDE-505039B

FEATURES

- 3.4 to 5.0 GPM / 3000 to 5000 PSI
- 13 to 24 HP gasoline engines; 10 HP Diesel engine or 20 HP motor
- Available in small cage (2-wheel) or large cage (4-wheel) frame design
- Recoil or electric-start gas-engine models

BD / BDE SERIES Cold Water Models

The Hotsy BD / BDE Series: The Right Choice for Tough, Cold-Water Cleaning

BD SPECIFICATIONS - Gasoline Models

BELT DRIVE

■ 3.4 to 5.0 GPM @ 3000 to 5000 PSI

■ 2 or 4-wheel frames

■ Recoil or electric-start gas engines

■ ETL Certified

MODEL	GPM	PSI	CC's (HP)	ENGINE	START	TRIPLEX PUMP MODEL	FRAME	NO. WHEELS	HOSE	SHIP WT (lbs)
BD-373539	3.7	3500	389 (13)	Honda GX Gas	RECOIL	HM4035R.2	Small Cage	2	50'	290
BD-404029	4.0	4000	479 (16)	Vanguard Gas	RECOIL	HHC930R.1	Large Cage	4	50'	360
BD-405039E*	4.0	5000	614 (20)	Honda GX Gas	ELECTRIC	HH5050R	Large Cage	4	50'	417
BD-455039E*	4.5	5000	670 (24)	Honda GX Gas	ELECTRIC	HH5050R	Large Cage	4	50'	430
BD-343089E*	3.4	3000	401 (9.8)	Kohler KD Diesel	ELECTRIC	HM3540R.2	Large Cage	4	50'	410

*Battery required, but not supplied

Dimensions: *Small cage:* 42"L x 26"W x 30"H / *Large cage:* 46"L x 30"W x 36"H

BDE SPECIFICATIONS - Electric Models

BELT DRIVE

■ 5.0 GPM @ 5000 PSI

■ 20 HP Electric Motor

■ 4-wheel frames

■ NEMA 4-Electrical Box

■ ETL Certified

MODEL	GPM	PSI	HP	MOTOR RPM	VOLT / PH	AMPS	TRIPLEX PUMP MODEL	PUMP PRM	NO. WHEELS	CORD LENGTH	HOSE	SHIP WT (lbs)
BDE-505039B	5.0	5000	20	1750	230 / 3	48	HH5050R	1650	4	12'	50'	480
BDE-505039C	5.0	5000	20	1750	460 / 3	26	HH5050R	1650	4	12'	50'	480

Large cage: 46"L x 30"W x 36"H

OPTIONS

- Large or small cage 100' E-Zee Hose Reel Kit*
- Large Cage 5000 PSI Hose Reel Kit*
- Large Cage 5000 PSI Dual Hose Reel Kit**

* Kit includes hose reel and mounting hardware

† Includes garden hose reel and high-pressure hose reel



Clean better with Hotsy detergents

Hotsy pressure washers clean best when matched with our specially-formulated Hotsy detergents. Nearly all 40 Hotsy detergent formulations contain Hotsy's exclusive advanced-formula HCC additives to help prevent scale build-up and fight corrosion in your equipment. Most Hotsy detergents are USDA and Canadian Agriculture approved, and all are highly concentrated, so a little goes a long way.

Hotsy Accessories customize your application for top performance



360° Pivot and non-pivot hose reels



High-pressure turbo nozzles for faster cleaning

Telescoping wands extend to 24' to reach high places without scaffolding



High-pressure hoses from 30 to 150-ft. lengths



Rotary surface cleaner attaches to your pressure washer; reduces overspray and zebra striping

Distributed by:

hotsy *Nothing Cleans Like a Hotsy!*

Tel: (800) 525-1976 Fax: (888) 880-9631
www.Hotsy.com email: info@Hotsy.com



P/N 8.914-197.0 Effective 10/09 Specifications and product descriptions subject to change without notice. ©2008 Hotsy

NOTE: We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We attempt to keep our machine performance within ± 5% of listed specifications.